



NO.	PART NO.	DESCRIPTION
1	14006	CUSHION - BASE
2	14007	BASE
3	14008	1/4" X 20 NUT
4	14009	UPRIGHT ROD
5	14010	MAGNET ASS'Y
6	14013	LOCK WASHER
7	14011	#8-32 X 5/16" SCREW
8	14012	CLIP-HANDLE

#### TOOLS NEEDED FOR ASSEMBLY

- Slot Head Screw Driver
- 7/16" Open End Wrench

#### TO ASSEMBLE STAND:

1. Peel backing from adhesive on pad (1) and adhere to bottom of base (2).
2. Thread nut (3) completely onto upright rod (4). Then thread upright rod into base (2).
3. Position upright rod (4) so bend is facing Smith name on base (2). Then with wrench, tighten nut (3) to lock upright rod (4) in place.
4. Place magnet assembly (5) on upright rod (4) and secure with screw and lock washer (6 & 7). Tighten screw with slot head screw driver.

#### TO APPLY CLIP ASSEMBLY TO TORCH:

1. Loosen torch handle (counter clockwise) and slide back from torch head.
2. Insert clip assembly (8) into torch assembly, position opposite valves as shown in drawing and tightly snug handle on clip to hold into place.

**WARNING:** Be sure the clip assembly on the torch makes full contact with the magnet assembly when being used, or the torch may fall from the base causing possible personal injury and/or property damage.